



Louvers & Gauges

Product Specifications

Greschner™ Sight Gauge / Rate Gauge

Model No. SG48BC

Highlights

- Full length flanges allow for easy installation
- Gauge lengths available from 6-inches (15cm) to 20-feet (6m) in length.
- Calibrations in Litres/24-Hours. & Height in Centimetres.
- Red line behind glass tube allows for fast and accurate reading of clear liquids.
- Comes standard with Buna seals. (Other seals available.)
- Comes standard with 3/8-inch NPT internal & 1/2-inch NPT external carbon steel fittings. (Stainless Steel and PVC fittings available.)
- Comes standard with breather cap on top fitting.

· Repair kit available, includes:

- (1) - Glass tube
- (1) - Plexi shield
- (2) - O-ring seal of specified type
- (2) - Set screws
- (1) - Breather cap



Above: Greschner™ SG48BC

Installation

The Sight Gauge / Rate Gauge should be mounted to the building or support bracket using metal fasteners.

Note:

Louvers & Gauges makes every effort to ensure the accuracy of their gauges. Measurement variances may occur due to fluctuations in temperature, fluid viscosities and manufacturers tolerances in the glass tubing, if measurements are being taken over a long period of time. Therefore, it is the responsibility of the user / operator to record large volumes of material being pumped as an accurate calibration, when compared to a one minute test.

Louvers & Gauges

Office: (780) 440-6653

Fax: (780) 466-4253

Cell: (780) 619-3402

9732 - 27 Avenue

Edmonton, Alberta

Canada T6N 1B2